



PORTA CONTOURS

know & love
timber

Timber Lining Boards

Add warmth, texture
& style to any room

Ideal for internal wall
lining applications



Contours Profile: Crest (Wall), Cirque (Bedhead)



Porta Contours is a stylish new range of timber lining profiles that will add warmth, and texture to any room.

Porta Contours, inspired by the contours of the beautiful Australian landscape are available in 6 profiles as well as custom designed lining board designs in Select grade Tasmanian Oak hardwood and other certified timber species.



Contours Profile: Cirque



Wattyl 270-062 Walnut timber stain

Contours Profile: Strata

Clear matte stain




Select Grade
Made in select grade certified Tasmanian Oak timber



Easy to Install
Tongue & groove can be direct fixed




Reduced Costs
Boards reduce installation costs on site (direct fix frame)



Stocked lengths available & Made to Order (MOQ apply)
Stocked lengths: 1.8 and 2.7m.
MTO for 300 LM+



Range of Applications
Residential, commercial, hospitality & more



Staining & Coating
Specify a product colour code / reference for matching



Custom Design
Available on request

Porta Contours Product Range Overview



	RIVERINE	CIRQUE	CREST	STRATA	PLATEAU-78	PLATEAU-39
Part No.	LINA7821	LINB7821	LINC7821	LIND7821	LINE7812	LINE3912
Cover Width	78mm	78mm	78mm	78mm	78mm	39mm
Board Size	91 x 21mm	91 x 21mm	91 x 21mm	91 x 21mm	91 x 12mm	52 x 12mm

*Available in a range of certified timber species.



1300 650 787 sales@porta.com.au porta.com.au

How to specify Porta Contours

Product: Porta Contours + profile name + length. E.g. Porta Contours – Riverine – 1.8m

Timber Lining Boards shall be Porta Contours supplied with PEFC™ [or FSC, as applicable] certification and written product information. Hardwood lining boards shall comply with AS 2796 Section 6: Lining Boards. Softwood lining boards AS 4785.1 Section 5: Lining Boards.

Finish: Porta offer clear finish and timber colour staining. Specify a timber colour code or reference for matching. Porta recommend pre-staining and tinting to ensure a quality finish and movement of boards once installed. MOQ apply for coatings. Max length for coating 3.6m

Certification: Porta will provide proof the timber species specified is Certified and sourced from responsibly managed forests.

Preparation & Installation

Ensure the backing surface is structurally sound, dry, free of dust, grease and oil. If the backing is painted, remove any loose or flaking paint film.

Apply construction adhesive or fix at a maximum of 450mm centres.

Either fix with a deep drive brad or, for harder timber, pre-drill and use a finishing nail. If using adhesive alone, ensure boards are physically supported until the adhesive has cured.

Technical Information - Fire Performance

Material: Tasmanian Oak (Kiln Dried)

Fire Properties Group Number*: 3

Average Specific Extension Area: >250m²/kg

Critical Radiance Flux: 72.2 and <4.5kW/m²

Smoke Developed Index: <75%/Min

*Tested in accordance with the requirements of NCC specification C1.10



Contours Profile: Crest



Contours Profile: Riverine

More Information

Please call us to discuss your requirements, arrange a meeting or a sample.



1300 650 787 sales@porta.com.au porta.com.au





know & love
timber

1300 650 787

sales@porta.com.au

porta.com.au



Contours Profile: Strata (Wall), Riverine (Back Wall),
Riverine & Plateau-39 (Bar)



Contours Profile: Crest



Contours Profile: Crest



Contours Profile: Riverine



Image: Dulux Australia. Photographer: Mike Baker. Stylist: Bree Leech.



Image: Dulux Australia. Photographer: Mike Baker. Stylist: Bree Leech.

people who know & love timber